



Wireless Capabilities



Optional Portable Handheld Indicator



Large Easy to Read LCD Display

CCB SERIES

Crane Scale

The CCB Series Crane Scale is a full featured, rugged industrial crane scale with a backlit LCD display suitable for viewing even in direct sunlight! The CCB Series is available in capacities ranging from 2,000 to 20,000 lbs.

- Easy to Read
- Easy to Use
- Accurate
- Versatile
- Unquestionably Safe
- Durable Long Life



CCB Series ▶

CAS

www.cas-usa.com

CCB SERIES | Crane Scale

SPECIFICATIONS

Model		CCB-1TLF	CCB-3TLF	CCB-5TLF	CCB-10TLF
Weighing Capacity	lb	2,000 x 0.5 lb	5,000 x 1 lb	10,000 x 2 lbs	20,000 x 5 lbs
	kg	1,000 x 0.2 kg	2,500 x 0.5 kg	5,000 x 1 kg	10,000 x 2 kg
Enclosure	Aluminum Die Casting				
Accuracy	0.1% of Applied Load up to Full Capacity				
Display Digit	6 Digit 1.18" inch / 30 mm LCD with Backlight				
Keys	5 Button Keypad - On/Off, Zero, Tare, Kg/lb, *				
Safety Overload	200% of Capacity				
Power Source	3.7VDC Lithium Polymer Battery				
Operating Time	Approximately 300 hours				
Operating Distance	CRC-100 Handheld Indicator - Approx 100 m / 328 ft				
Operating Temp	-20°C ~ 60°C / -4°F ~ 140°F				
Product Weight		19.6 lbs / 8.9 kg	33.5 lbs / 15.2 kg	36.8 lbs / 16.7 kg	59.3 lbs / 26.9 kg

FEATURES

Standard features of the CCB SERIES include an on-board, backlit LCD display with easy to read 1 3/16" (30mm) display characters, an infrared remote controller, swivel hook, and a long lasting, easy to change lithium polymer battery (Li-Po).

For more demanding applications, the CCB Series Crane Scale is also available with options including the ready to use CRC-100 wireless portable handheld indicator with data management & RS232 connectivity capabilities, and the wireless 2.3" and 3" FND Remote Display Units.

Included with each scale

- Crane Scale
- Two lithium polymer rechargeable batteries with charger
- IR remote control

Options

- CRC-100 Wireless Portable Handheld Indicator
- CRD Wireless Remote Displays



▲ Optional Wireless Remote Displays with Tilt Mounting Brackets and IR Remote Control



DIMENSIONS

Item #		Dimensions (mm/inches)
CCB-1TLF	Inches	8.6 (W) x 10 (D) x 16 (H)
	mm	219 (w) x 253 (D) x 407 (H)
CCB-3TLF	Inches	8.6 (W) x 10 (D) x 20.7 (H)
	mm	219 (w) x 253 (D) x 526 (H)
CCB-5TLF	Inches	8.6 (W) x 10 (D) x 20.7 (H)
	mm	219 (w) x 253 (D) x 526 (H)
CCB-10TLF	Inches	8.6 (W) x 10 (D) x 27.4 (H)
	mm	219 (w) x 253 (D) x 696 (H)
CRD-2300F	Inches	14.1 (W) x 4.5 (H) x 6.9 (D)
	mm	358 (W) x 115 (H) x 176 (D)
CRD-3000F	Inches	17.6 (W) x 5.6 (H) x 7.2 (D)
	mm	447 (W) x 141 (H) x 183 (D)
CRC-100	Inches	3.8 (W) x 8.1 (H) x 1.9 (D)
	mm	95 (W) x 205 (H) x 48 (D)

The backlit LCD wireless CRC-100 handheld indicator is easy to see and to use. It features a 15 key keypad (zero, tare, hold, stable, low battery), wireless ZigBee communication, memory for data management (70 items and customers), and RS232 connectivity.

◀ CRC-100 Wireless Portable Handheld Indicator

Construction	Plastic
Display	LCD (15mm/0.6 inches) with backlight
Display Designators	Zero, Tare, Hold, Stable, Low Battery
Keypad	15 Keys
Battery Life	Approx 90 hrs
Operating Temp	-20°C ~ 60°C / -4°F ~ 140°F
Power	3.7VDC Lithium Polymer Battery
Product Weight	1 lb / 0.5 kg



99 Murray Hill Parkway
East Rutherford, NJ 07073
Toll Free: (800) 223-4227
Tel: (201) 933-9002
Fax: (201) 933-9025
http://www.cas-usa.com

Specifications are subject to change for improvement without prior notice.